

Annex to Solar Keymark Certificate					Licence Number		011-7S3149 F							
					Date issued		2022-11-14							
					Issued by		DIN CERTCO							
Licence holder		Remon Technische Groothandel			Country		Netherlands							
Brand (optional)					Web		www.remon-techniek.nl							
Street, Number		Schakelstraat 4			E-mail		inkoop@remon.com							
Postcode, City		NL- 9363 TH Marum			Tel		31 594-648080							
Collector Type					Flat plate collector									
Collector name					Power output per collector									
					Gb = 850 W/m ² , Gd = 150 W/m ² & u = 1.3 m/s $\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	88 K				
					m ²	mm	mm	mm	mm	mm	mm			
Remontec 2530					2.53	2 102	1 202	80	1 856	1 762	1 556	1 327	1 072	823
Power output per m² gross area					735	697	616	525	424	326				
Performance parameters test method		Steady state - indoor												
Performance parameters (related to A_G)		η_0, b	a1	a2	a3	a4	a5	a6	a7	a8	Kd			
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-			
Test results		0.748	3.59	0.012			5 660				0.88			
Incidence angle modifier test method		Quasi dynamic - outdoor												
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°			
Transversal		K _{θT, coll}	1.00	0.99	0.98	0.96	0.93	0.87	0.75	0.37	0.00			
Longitudinal		K _{θL, coll}	1.00	0.99	0.98	0.96	0.93	0.87	0.75	0.37	0.00			
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A_G)					dm/dt		0.020	kg/(sm ²)						
Maximum temperature difference during thermal performance test					$(\vartheta_m - \vartheta_a)_{max}$		58	K						
Standard stagnation temperature (G = 1000 W/m²; $\vartheta_a = 30$ °C)					ϑ_{stg}		200	°C						
Maximum operating temperature					$\vartheta_{max, op}$		100	°C						
Maximum operating pressure					p _{max, op}		1000	kPa						
Testing laboratory		ISFH CalTeC			https://isfh.de/									
Test report(s)		153-22/B			Dated		14.11.2022							
Comments of testing laboratory					Ver. 6.2 (13.01.2022)									
					Institut für Solarenergieforschung GmbH Am Ohrberg 1 D-31880 Emmerthal Tel.: 05151/999-100 Fax: 05151/999-500									
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de														

Annex to Solar Keymark Certificate		Licence Number												
Supplementary Information		011-7S3149 F												
		Issued												
		2022-11-14												
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m														
	Standard Locations	Athens			Davos			Stockholm			Würzburg			
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	
Remontec 2530		2 916	2 049	1 316	2 200	1 500	927	1 621	1 046	622	1 762	1 126	660	
Gross Thermal Yield per m ² gross area		1 154	811	521	871	594	367	641	414	246	697	446	261	
Annual efficiency, η_a		65%	46%	30%	53%	36%	23%	55%	35%	21%	56%	36%	21%	
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)												
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²			
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C			
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°			
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.2 (13.01.2022). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/														
Additional Information														
Collector heat transfer medium											Water-Glycole			
The collector is deemed to be suitable for roof integration											No			
The collector was tested successfully under the following conditions:														
Climate class (A+, A, B or C)											A		--	
G (W/m ²) >		1000		ϑ_a (°C) >		20		H _x (MJ/m ²) >		600				
Maximum tested positive load											3030		Pa	
Maximum tested negative load											2800		Pa	
Hail resistance using steel ball (maximum drop height)											2		m	
Additional collector attribute(s)														
Using external power source(s) for normal operation											No		Active or passive measure(s) for self-protection	No
Co-generating thermal and electrical power											No		Façade collector(s)	No
Energy Labelling Information							Additional Informative Technical Data							
Reference Area, A _{sol} (m ²)							Hydraulic Designation Code				Aperture Area, A _a (m ²)			
Remontec 2530							1-VH-12S-A:11.3,17042				2.36			
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}							Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}							
Collector efficiency (η_{col})							Zero-loss efficiency (η_0)				0.73			--
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.							First-order coefficient (a ₁)				3.59			W/(m ² K)
							Second-order coefficient (a ₂)				0.012			W/(m ² K ²)
							Incidence angle modifier IAM (50°)				0.92			--
							Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.							
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany														
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de														